YTO C502 Crawler Tractor

Model		YTO C502 Crawler Tractor
Parameters		
Туре		Agricultural crawler type
Dimension(LengthxWidthxHeight) (With earthmoving shovel)	mm	3760x2016x1680
Min. operating weight(With earth-moving shovel)	Kg	3670
Wheeltread	mm	1100
Wheelbase	mm	1600
Width of crawler	mm	310
Ground specific pressure(with shovel)	kPa	36.9
Diesel engine		
Model		YT3B2
Туре		Vertical,water-cooling,four-stroke
Displacement	L	3.3
Rated power and speed	Kw/r/min	36.7/2200
Transmission		
Gears forward/rear		8/4
Speed forward/rear	Km/h	1.81-12.78/2.01-6.05
Power of power takeoff shaft	Kw/r/min	31
Speed of PTO	r/min	540/720
Clutch		11-inch double-disc double-action
Work attachments		
Type pf three-point linkage		Rear-mounted two-point or three- point class-II linkage
Depth-control method		Height adjustment
Lifting force	Kn	8
Size of earth-moving shovel (Width x Height)	mm	2016x680
Underground depth of earth-moving shovel	mm	260

YTO C502 Crawler Tractor

Model	YTO C502 Crawler Tractor
Parameters	
Туре	Agricultural crawler type



YTO C502 Crawler Tractor

Product name: YTO C502 Crawler Tractor
Engine power: 50 horse power
Engine brand & model: YTO YT3B2
Min Order Qty: 1 unit
Delivery Time: 35 days
Country of Origin: China

- 1. Suitable for operations in agricultural land and orchard, and small-quantity earth-moving operation as well.
- 2. Dry-type double-disc disc-spring-compressed double-action main clutch, which is easy to operate.
- 3. Transmission composed of engagement sleeve based gear shifting mechanism (2+1)x4,which has a lot of gears, and is easy to control and suitable for various operations.
- 4. Multi-disc dry-type steering clutch of which the friction discs are made of new material and have long service life, and floating-type belt brake which enables reliable braking operation.
- 5. Semi-steel suspension system, which increases the earth-moving performance.

