YTO C802 Crawler Tractor

Model		YTO C802 Crawler Tractor
Parameters		
Туре		Agricultural crawler type
Dimension(LengthxWidthxHeight) (With earthmoving shovel)	mm	4870x2462x2766
(Without earth-moving shovel)	mm	4466x1835x2766
Min. operating weight	Kg	6630(equipped with earth-moving shovel)
Wheeltread	mm	1435
Wheelbase	mm	1622
Width of crawler	mm	390
Ground specific pressure	kPa	47.4(equipped with earth-moving shovel)
Diesel engine		
Model		LR4A3Z-22
Туре		Vertical,water-cooling,four- stroke,turbocharged
Displacement	L	4.33
Rated power and speed	Kw/r/min	58.8/2200
Transmission		
Gears forward/rear		4/2
Speed forward/rear	Km/h	3.67-9.03/3.51-5.59
Power of power takeoff shaft	Kw/r/min	49
Speed of PTO	r/min	750
Clutch		12-inch double-disc single-action
Work attachments		
Type pf three-point linkage		Rear-mounted two-point or three- point class-II linkage
Depth-control method		Height adjustment
Lifting force	Kn	14
Size of earth-moving shovel (Width x Height)	mm	2462x850
Underground depth of earth-moving shovel	mm	290

YTO C802 Crawler Tractor

Model	YTO C802 Crawler Tractor
Parameters	
Туре	Agricultural crawler type



YTO C802 Crawler Tractor

Product name: YTO C802 Crawler Tractor
Engine power: 80 horse power
Engine brand & model: YTO LR4A3Z-22
Min Order Qty: 1 unit
Delivery Time: 35 days
Country of Origin: China

- 1. Tractor with new apperance, which can be widely used in agricultural land operations and earth-moving operation.
- 2. Dry-type double-disc single-action main clutch, which is easy to operate and has long service life.
- 3. 4+2 transmission equipped with sliding gear for shifting operation, which has reliable performance..
- 4. Multi-disc dry-type steering clutch, and floating-type belt brake which enables reliable braking operation.
- 5. Simply-supported beam stucture for final drive, which has the advantages including high supporting strength and high reliability.
- 6. Power-assisted hydraulic steering system, which will reduce the labor intensity of operator.
- 7. Wide crawler available for works on low and wet land, and rubber crawler available for increasing the trafficability.

