

# YTO-X704 Wheeled Tractor



## YTO-X704 Wheeled Tractor Technical Specification

<b>Model</b>	<b>YTO-X704</b>
Type	4×4
Dimension(LxWxH) (mm)	4250×2145×2650
Wheelbase (mm)	2314
Min. Ground clearance (mm)	370
Min. operation mass (Kg)	3540
Type specification front wheel/rear wheel	11.2-24/16.9-30
Wheel track front/rear (mm)	1569~2005/1500~2100
Steering device	Hydraulic
Brake	disc and oil bath type
<b>Diesel engine</b>	
Model	LR4B3-23
Type	4-cylinder, vertical, water cooling, 4-stroke, direct injection combustion chamber
Displacement (L)	4.33
Rated power & rotation (Kw)/(r/min)	51.5/2300
Max.torque(N.m)/rotation (r/min)	237/1500-1700
Bore & stroke (mm)	105x125
Rated working condition fuel consumption (g/kW·g)	≤235(with fan)
Rated working condition oil consumption (g/kW·g)	≤1.63(after running-in)
<b>Gearbox</b>	
Gearbox shift No. forward/reverse	12/4
Speed (Km/h) forward/reverse	1.61~26.57/4.19~12.59
PTO power(Kw)	44
PTO rotation(r/min)	540/1000
Clutch	11 inch
<b>Working device</b>	
Three point hitch type	Rear position three point II class
Tillage depth control mode	Power & position combined control and float control
Lifting capacity (KN)	≥16