

Model	YTO-X704 Tractor	YTO-X754 Tractor	YTO-X804 Tractor	YTO-X854 Tractor	YTO-X904 Tractor
Type	4x4	4x4	4x4	4x4	4x4
Overall dimensions (LxWxH) (mm)	4250x2145x2650	4250x2145x2650	4350x2170x2740	4350x2170x2740	4350x2300x2765
Wheelbase (mm)	2314	2314	2314	2314	2314
Min. ground clearance (mm)	370	370	430	430	440
Min. operating mass (with safety stand) (Kg)	3540	3540	3675	3675	3920
Tyre spec. front/rear	11.2-24 / 16.9-30	11.2-24 / 16.9-30	11.2-28 / 13.6-38	11.2-28 / 13.6-38	13.6 -24 / 16.9-34
Wheel tread, front/rear	1569-2005/1500-2100	1569-2005/1500-2100	1630-1960/1500-2100	1630-1960/1500-2100	1562-2000/1520-2120
Steering	Full hydraulic	Full hydraulic	Full hydraulic	Full hydraulic	Full hydraulic
Brake	Oil immersed, disk type	Oil immersed, disk type	Oil immersed, disk type	Oil immersed, disk type	Oil immersed, disk type
Diesel engine					
Model	LR4A3-23	LR4B5-23	LR4B5-23	LR4B5-23	LR4M5-23
Type	Four cylinder, vertical, water cooled, four stroke, direct injection combustion	Four cylinder, vertical, water cooled, four stroke, direct injection combustion	Four cylinder, vertical, water cooled, four stroke, direct injection	Four cylinder, vertical, water cooled, four stroke, direct injection combustion	Four cylinder, vertical, water cooled, four stroke, direct injection combustion
Displacement (L)	4.33	4.95	4.95	5.13	5.13
Rated power / speed (Kw) / (r/min)	51.5 / 2400	55 / 2400	58.8 / 2300	62.5 / 2400	66.5 / 2300
Max. torque (N.m) / speed (r/min)	237 / 1500-1700	254 / 1500-1700	270 / 1500-1700	302 / 1600-1800	325 / 1600-1800
Bore x stroke (mm)	105 x 125	105 x 125	108 x 125	108 x 135	110 x 135
Transmission					
Gear shift, forward / backward	12/4	12/4	12/4	12/4	12/4
Speed range (Km/h), forward / backward	1.61-26.57/4.19-12.59	1.61-26.57/4.19-12.59	1.63-26.82/4.23-12.69	1.63-26.82/4.23-12.69	1.65-27.17/4.28-12.85
PTO power (Kw)	44	47	50	50	55

Model	YTO-X704 Tractor	YTO-X754 Tractor	YTO-X804 Tractor	YTO-X854 Tractor	YTO-X904 Tractor
Type	4x4	4x4	4x4	4x4	4x4
Overall dimensions (LxWxH) (mm)	4250x2145x2650	4250x2145x2650	4350x2170x2740	4350x2170x2740	4350x2300x2765
PTO rotation speed (r/min)	540/720 or 540/1000	540/720 or 540/1000	540/720 or 540/1000	540/720 or 540/1000	540/720 or 540/1000
Clutch	11-inch, dry, double action	11-inch, dry, double action	11-inch, dry, double action	11-inch, dry, double action	11-inch, dry, double action
Implement					
Three-point linkage category	Three-point linkage category II	Three-point linkage category II	Three-point linkage category II	Three-point linkage category II	Three-point linkage category II
Tilling depth control mode	Combined draft, position control and floating control	Combined draft, position control and floating control	Combined draft, position control and floating control	Combined draft, position control and floating control	Combined draft, position control and floating control
Lifting force (KN)	16	16	16	16	17
Options					
OECD anti-turnover bar	OECD certified anti-turnover bar or anti-turnover bar with awning	OECD certified anti-turnover bar or anti-turnover bar with awning	OECD certified anti-turnover bar or anti-turnover bar with awning	OECD certified anti-turnover bar or anti-turnover bar with awning	OECD certified anti-turnover bar or anti-turnover bar with awning
Transmission with shuttle-type gear	12+12	12+12	12+12	12+12	12+12
Transmission with creeper gear	24+8	24+8	24+8	24+8	24+8
Hydraulic output	2 or 3 group	2 or 3 group	2 or 3 group	2 or 3 group	2 or 3 group

YTO 70hp to 90hp 4WD Wheeled Tractor

Model: YTO X704/X754/X804/X854/X904 Wheeled Tractor

Engine rated power: 51.5kw/55kw/58.8kw/62.5kw/66.5kw

Engine brand: YTO

Engine: LR4A3-23/LR4B5-23/LR4B5-23/LR4M5-23/LR4M5-23

Driving type: 4WD

The YTO X704/X754/X804/X854/X904 Wheeled Tractor is developed on the basis of the Italian wheeled tractor chassis technology, adopting the British technology-based 4-cylinder turbo-charged engine. The machine body has a streamline configuration. The tractor has low specific fuel consumption and desirable energy efficiency. It has multiple gears and a wide speed range. Besides, it is flexible in steering and easy to operate.



SunnForest Enterprises