

YTO C1302 Crawler Tractor

Model		YTO C1302 Crawler Tractor
Parameters		
Type		Agricultural crawler type
Dimension(LengthxWidthxHeight) (With earth-moving shovel)	mm	5367x2462x2910
Min. operating weight (With earth-moving shovel)	Kg	7300
Wheeltrack	mm	1435
Wheelbase	mm	1792
Width of crawler	mm	390
Ground specific pressure	kPa	47.7(equipped with earth-moving shovel)
Diesel engine		
Model		LR6A3Z
Type		Vertical,water-cooling,four-stroke,turbocharged
Displacement	L	6.49
Rated power and speed	Kw/r/min	95.6/2200
Transmission		
Gears forward/rear		6/2
Speed forward/rear	Km/h	3.71-13.90/3.31-6.28
Power of power takeoff shaft	Kw/r/min	81
Speed of PTO	r/min	540/1000
Clutch		14-inch double-disc single-action
Work attachments		
Type pf three-point linkage		Rear-mounted two-point or three-point class-II linkage
Depth-control method		Height adjustment
Lifting force	Kn	14.6
Size of earth-moving shovel (Width x Height)	mm	2462x850
Underground depth of earth-moving shovel	mm	330

YTO C1302 Crawler Tractor

Model		YTO C1302 Crawler Tractor
Parameters		
Type		Agricultural crawler type



YTO C1302 Crawler Tractor

Product name: YTO C1302 Crawler Tractor

Engine power: 130 horse power

Engine brand & model: YTO LR6A3Z

Min Order Qty: 1 unit

Delivery Time: 35 days

Country of Origin: China

1. Tractor with optimized design and new appearance, which is mainly used for plowing and harrowing operations and is also suitable for earth-moving operation.
2. Dry-type double-disc disc-spring-compressed, 10-inch main clutch, which is equipped with damping spring and has long service life.
3. 6+2 transmission equipped with engagement sleeve for shifting operation, which has reliable performance and reduces the force required to operate it.
4. Multiple-disc dry-type steering clutch of which the friction discs are made of new material and have long service life, and floating-type belt brake which enables reliable braking operation.
5. Optimally-arranged control mechanism, power-assisted hydraulic steering system, and self-lubricating shaft sleeve, which can reduce the operating force and maintenance points.
6. Fully-enclosed cab, which can be equipped with air conditioner at the request of customer.
7. Rubber crawler available as an option for increasing the trafficability.

SunnForest Enterprises