

## YTO C602 Crawler Tractor

Model		YTO C602 Crawler Tractor
<b>Parameters</b>		
Type		Agricultural crawler type
Dimension(LengthxWidthxHeight) (With earth-moving shovel)	mm	3760x2016x1680
Min. operating weight(With earth-moving shovel)	Kg	3700
Wheel tread	mm	1100
Wheelbase	mm	1600
Width of crawler	mm	310
Ground specific pressure(with shovel)	kPa	37.2
<b>Diesel engine</b>		
Model		YT3B2
Type		Vertical,water-cooling,four-stroke
Displacement	L	3.3
Rated power and speed	Kw/r/min	44/2400
<b>Transmission</b>		
Gears forward/rear		8/4
Speed forward/rear	Km/h	1.97-13.94/2.20-6.60
Power of power takeoff shaft	Kw/r/min	37
Speed of PTO	r/min	540/720
Clutch		11-inch double-disc double-action
<b>Work attachments</b>		
Type pf three-point linkage		Rear-mounted two-point or three-point class-II linkage
Depth-control method		Height adjustment
Lifting force	Kn	8
Size of earth-moving shovel (Width x Height)	mm	2016x680
Underground depth of earth-moving shovel	mm	260

## YTO C602 Crawler Tractor

Model		YTO C602 Crawler Tractor
Parameters		
Type		Agricultural crawler type



## YTO C602 Crawler Tractor

Product name: YTO C602 Crawler Tractor

Engine power: 60 horse power

Engine brand & model: YTO YT3B2

Min Order Qty: 1 unit

Delivery Time: 35 days

Country of Origin: China

1. Suitable for operations in agricultural land and orchard, and small-quantity earth-moving operation as well.
2. Dry-type double-disc disc-spring-compressed double-action main clutch, which is easy to operate.
3. Transmission composed of engagement sleeve based gear shifting mechanism (2+1)x4, which has a lot of gears, and is easy to control and suitable for various operations.
4. Multi-disc dry-type steering clutch of which the friction discs are made of new material and have long service life, and floating-type belt brake which enables reliable braking operation.
5. Semi-steel suspension system, which increases the earth-moving performance.